

Unclassified

Defense Documentation Center

Defense Supply Agency

Cameron Station • Alexandria, Virginia

N66 21769

ACCEDED ON DATE
83

PAGES
1

CR - 71410

(NASA CR OR TMX CR ADDITION NUMBER)

ITEM NO.

CODE

CATEGORY

09



GPO PRICE \$ _____

CFSTI PRICE(S) \$ _____

Hard copy (HC) \$ 3.00

Microfiche (MF) \$ 1.75

SECURITY MARKING

The classified or limited status of this report applies to each page, unless otherwise marked.
Separate page printouts **MUST** be marked accordingly.

THIS DOCUMENT CONTAINS INFORMATION AFFECTING THE NATIONAL DEFENSE OF THE UNITED STATES WITHIN THE MEANING OF THE ESPIONAGE LAWS, TITLE 18, U.S.C., SECTIONS 793 AND 794. THE TRANSMISSION OR THE REVELATION OF ITS CONTENTS IN ANY MANNER TO AN UNAUTHORIZED PERSON IS PROHIBITED BY LAW.

NOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may or may not be related thereto.

L-747 REPORT SUMMARY SHEET

Semiconductor Transistor, Switching, Silicon NPN		MANUFACTURER REPORT NO. Saturn	C D E	
Semiconductor Device Qualification Test, General Specification		TEST REPORT NO. 111263-8-1	TEST DATE 1968-07-10	
THIS TEST REPORT COVERS (INPUT) EVENTS REPORT NO.		EVALUATION		
1. USA PART TYPE, SIZE, RATING, LOT, ETC.		VENDOR	2. VENDOR PART NO.	3. MFG. AND TEST NO.
1. 150 w Stud Mounted		Westinghouse	2N4343	100
2. 150 w Stud Mounted				
3. 150 w Stud Mounted				
4. INTERNAL SPEC CITE REQS TO OTHERS REF. ENCL.		NEXT MFG REPORT NO.	14. MIL-SPEC STD. REFERENCED IN SEC.	
1. SOD1350TA-33		X	MIL-S-1050	
2. SOD1350TA		742 36 34.00-H1-02	MIL-S-730	
5. TEST OR ENVIRONMENT		C D SPEC. PARAMETERS PER SPEC	E TEST LEVELS, DURATION AND OTHER DETAILS	
1. Seal Leak Test		B 4.1.1	Radioactive Tracer Gas	
2. Visual (Ext)		B 4.1.2	10 Power Magnification	
3. Physical Dimen.		B 3.3	As per Drawing	
4. Visual (Int)		B 4.1.2.2	10 Power Magnification	
5. Group A Parameters		A Table II	Electrical Measurements	
6. Operating Life		B 4.3.1	TC = 88°C PT = 83 Watt Duration 2000 hours	
7. 100 hour End Points		A Table IV	ΔICEX hFE ICE(sch)	
8. 200 hours End Points		A Table IV	ΔICEX hFE ICE(sch)	
9. 300 hours End Points		A Table IV	ΔICEX hFE ICE(sch)	
REASON OF REPORT, NATURE OF FAILURES AND CORRECTIVE ACTIONS TAKEN				
<p>✓ S/N's 93-100 excessive leakage.</p> <p>✓ S/N's 91 and 92 illegible markings.</p> <p>✓ S/N 2 failed ICEX. S/N 1 failed ICE. S/N's 1 and 83 failed hFE.</p> <p>✓ S/N's 4, 8, 9 and 90 were destroyed attempting to attain 150 watt dissipation.</p>				
15. TOTAL TESTS		16. APPROVAL		
17. APPROVAL		18. APPROVAL		
NASA/NFRC LARSEN INC.				
REPRODUCTION OR DISPLAY OF THIS MATERIAL FOR SALES OR PUBLICITY PURPOSES IS PROHIBITED.				

4725

TEST OR ENVIRONMENT		C PER SPEC	SPEC PARAGRAPH IN TEST CONDITION	TEST LEVEL, DURATION AND OTHER DETAILS		M TEST ITEM
1-1	1000 hour End-Points	A	Table IV	△ ICEX hFE rCE(sat)	10	0
1-2	1000 hour End-Points	A	Table IV	△ ICEX hFE rCE(sat)	10	0
1-3	2000 hour End-Points	A	Table IV	△ ICEX hFE rCE(sat)	20	0
1-4	Storage Life	B	4.3.2	TA = -175°C Duration 2000 hours		
1-5	100 hour End-Points	A	Table IV	△ ICEX hFE rCE(sat)	10	0
1-6	200 hour End-Points	A	Table IV	△ ICEX hFE rCE(sat)	10	0
1-7	500 hour End-Points	A	Table IV	△ ICEX hFE rCE(sat)	10	0
1-8	1000 hour End-Points	A	Table IV	△ ICEX hFE rCP(sat)	10	0
1-9	1500 hour End-Points	A	Table IV	△ ICEX hFE rCE(sat)	10	0
1-10	2000 hour End-Points	A	Table IV	△ ICEX hFE rCP(sat)	10	0
1-11	Altitude Test	B	4.3.3	200,000 ft. altitude, ICBQ monitored	20	0
1-12	Material Acceleration	B	4.3.4	NAL-STD-730, Method 1001	20	0
1-13	Portability End-Points	A	Table IV	△ ICEX hFE rCE(sat)	20	0
1-14	Solderability	B	4.3.5	NAL-STD-202C, Method 210, Condition S	20	0

2. EFFECTS OF TESTS

2.1 Exerted upon re-starting the test after 1500-hour End-Points.

2.2 Related to CIX

300-11-64

3-768

TEST NO. & DATE		TEST NO. & DATE		TEST NO. & DATE	
TEST NO. & DATE		TEST NO. & DATE		TEST NO. & DATE	
1		2		3	
4		5		6	
7		8		9	
10		11		12	
13		14		15	
16		17		18	
19		20		21	
22		23		24	
25		26		27	
28		29		30	
31		32		33	
34		35		36	
37		38		39	
40		41		42	
43		44		45	
46		47		48	
49		50		51	
52		53		54	
55		56		57	
58		59		60	
61		62		63	
64		65		66	
67		68		69	
70		71		72	
73		74		75	
76		77		78	
79		80		81	
82		83		84	
85		86		87	
88		89		90	
91		92		93	
94		95		96	
97		98		99	
100		101		102	
103		104		105	
106		107		108	
109		110		111	
112		113		114	
115		116		117	
118		119		120	
121		122		123	
124		125		126	
127		128		129	
130		131		132	
133		134		135	
136		137		138	
139		140		141	
142		143		144	
145		146		147	
148		149		150	
151		152		153	
154		155		156	
157		158		159	
160		161		162	
163		164		165	
166		167		168	
169		170		171	
172		173		174	
175		176		177	
178		179		180	
181		182		183	
184		185		186	
187		188		189	
190		191		192	
193		194		195	
196		197		198	
199		200		201	
202		203		204	
205		206		207	
208		209		210	
211		212		213	
214		215		216	
217		218		219	
220		221		222	
223		224		225	
226		227		228	
229		230		231	
232		233		234	
235		236		237	
238		239		240	
241		242		243	
244		245		246	
247		248		249	
250		251		252	
253		254		255	
256		257		258	
259		260		261	
262		263		264	
265		266		267	
268		269		270	
271		272		273	
274		275		276	
277		278		279	
280		281		282	
283		284		285	
286		287		288	
289		290		291	
292		293		294	
295		296		297	
298		299		300	
301		302		303	
304		305		306	
307		308		309	
310		311		312	
313		314		315	
316		317		318	
319		320		321	
322		323		324	
325		326		327	
328		329		330	
331		332		333	
334		335		336	
337		338		339	
340		341		342	
343		344		345	
346		347		348	
349		350		351	
352		353		354	
355		356		357	
358		359		360	
361		362		363	
364		365		366	
367		368		369	
370		371		372	
373		374		375	
376		377		378	
379		380		381	
382		383		384	
385		386		387	
388		389		390	
391		392		393	
394		395		396	
397		398		399	
400		401		402	
403		404		405	
406		407		408	
409		410		411	
412		413		414	
415		416		417	
418		419		420	
421		422		423	
424		425		426	
427		428		429	
430		431		432	
433		434		435	
436		437		438	
439		440		441	
442		443		444	
445		446		447	
448		449		450	
451		452		453	
454		455		456	
457		458		459	
460		461		462	
463		464		465	
466		467		468	
469		470		471	
472		473		474	
475		476		477	
478		479		480	
481		482		483	
484		485		486	
487		488		489	
490		491		492	
493		494		495	
496		497		498	
499		500		501	
502		503		504	
505		506		507	
508		509		510	
511		512		513	
514		515		516	
517		518		519	
520		521		522	
523		524		525	
526		527		528	
529		530		531	
532		533		534	
535		536		537	
538		539		540	
541		542		543	
544		545		546	
547		548		549	
550		551		552	
553		554		555	
556		557		558	
559		560		561	
562		563		564	
565		566		567	
568		569		570	
571		572		573	
574		575		576	
577		578		579	
580		581		582	
583		584		585	
586		587		588	
589		590		591	
592		593		594	
595		596		597	
598		599		600	
601		602		603	
604		605		606	
607		608		609	
610		611		612	
613		614		615	
616		617		618	
619		620		621	
622		623		624	
625		626		627	
628		629		630	
631		632		633	
634		635		636	
637		638		639	
640		641		642	
643		644		645	
646		647		648	
649		650		651	
652		653		654	
655		656		657	
658		659		660	
661		662		663	
664		665		666	
667		668		669	
670		671		672	
673		674		675	
676		677		678	
679		680		681	
682		683		684	
685		686		687	
688		689		690	
691		692		693	
694		695		696	
697		698		699	
700		701		702	
703		704		705	
706		707		708	
709		710		711	
712		713		714	
715		716		717	
718		719		720	
721		722		723	
724		725		726	
727		728		729	
730		731		732	
733		734		735	
736		737		738	
739		740		741	
742		743		744	
745		746		747	
748		749		750	
751		752		753	
754		755		756	
757		758		759	
760		761		762	
763		764		765	
766		767		768	
769		770		771	
772		773		774	
775		776		777	
778		779		780	
781		782		783	
784		785		786	
787		788		789	
790		791		792	
793		794		795	
796		797		798	
799		800		801	
802		803		804	
805		806		807	
808		809		810	
811		812		813	
814</					

Universal
Report No. 742.60.30.00-H1-04 Originator's
Report No. 11253-B-1

REPORT OF TEST ON Westinghouse 113D(2N3432) Transistor - Qualification


TEST PERFORMED BY:

CONTINENTAL TESTING LABORATORIES, INC.

TEST AUTHORIZED BY:

NASA/MSFC
Contract No. NAS8-11253

	Date	Signature
Test Initiated		
Test Completed		
Report Written By	3/30/65	Robert D. Stroh
Technician	3/30/65	Floyd G. Daniels
Test Engineer	3/30/65	Robert D. Stroh
Supervisor	3/30/65	Floyd C. King
Supervisor	4/2/65	Markus J. Brugel
Government Repr.	4/2/65	L. Dominick
Final Release	D.D.C.	



COPY FOR MICROFILMING

TABLE OF CONTENTS

	<u>Page</u>
Administrative Data	1
List of Apparatus	2
Summary	4
Table I	6
Table II	7
Table III	8
Visual Examination	9
Test Procedures and Results	10
Figure 1	11
Enclosure 1 - Summary Sheets	
Enclosure 2 - Data Sheets	
Enclosure 3 - Vendor's Comments	

ADMINISTRATIVE DATA

1. PURPOSE OF TEST

To subject the Westinghouse 113D (2N3432) Transistors to a series of environmental and electrical tests to qualify this type for possible use in the Saturn program equipment.

2. MANUFACTURER

Westinghouse Electric Corporation

3. MANUFACTURER'S TYPE OR MODEL NO.

113D (2N3432)

4. DRAWING, SPECIFICATION OR EXHIBIT

NASA 50M03501A/33 and MIL-STD-750

5. QUANTITY OF ITEMS TESTED

100

6. DATE TEST COMPLETED

February 5, 1965

7. SECURITY CLASSIFICATION OF ITEM

Unclassified

8. TEST CONDUCTED BY

Continental Testing Laboratories, Inc.,
755 U.S. Highway 17-92, Fern Park, Florida

9. DISPOSITION OF TEST SPECIMENS

Returned to NASA/MSFC, R-ASTR-RT, Attention: Mr. J. H. Smith

LIST OF APPARATUS

1. Power Supply, Lambda, Model #71.
2. Power Supply, Hyperion, Model #A1-32-10, S/N 129-228 A/76.
3. Transistor Test Station, Optimized Devices, Model #1500.
4. Vacuum Tube Voltmeter, Hewlett-Packard, Model #412A.
5. Vacuum Tube Voltmeter, Hewlett-Packard, Model #400H, S/N 313-22295.
6. Digital Voltmeter, Hewlett-Packard, Model #405BR.
7. Millivoltmeter, Hewlett-Packard, Model #411A.
8. Microvolt Ammeter, Hewlett-Packard, Model #425A, S/N 4859.
9. Differential Voltmeter, John Fluke, Model 803B, S/N 1736.
10. Wide Range Oscillator, Hewlett-Packard, Model #200CD, S/N 229-45217.
11. Pulse Generator, Hewlett-Packard, Model #214A, S/N 219.
12. Digital Counter, Hewlett-Packard, Model #50-5245L, S/N 335-00888.
13. Oscilloscope, Tektronix, Model #561-A, S/N 9979.
14. Potentiometer, Leeds & Northrup, Catalogue #8692, S/N 1629152.
15. Accelerometer, Endevco, Model 2215C, S/N FB-79.
16. Micrometer 1", Storrett, Model #436.
17. Sliding 6" Caliper, Storrett, Model #1025.
18. Soldering Pot, American Beauty, Catalogue #600.
19. ATC Timer, 1 second increment.
20. Tork Timer, 1 minute increment.
21. Vibration System, Ling Electronics.

LIST OF APPARATUS

22. Altitude Chamber, Consolidated Vacuum Corporation, Model FPC-40A.
23. Temperature Chambers, Continental Testing Laboratories, Inc., Models M12DR, M14DR, M16DH and M18DH.
24. Shock Machine, Continental Testing Laboratories, Inc., Model SH-5K.
25. High G Centrifuge, Continental Testing Laboratories, Inc., S/N 1028.
26. Modular Life Test Rack, Continental Testing Laboratories, Inc.
27. Discontinuity Time Monitor, Continental Testing Laboratories, Inc.

SUMMARY

DESCRIPTION OF ITEMS

The Westinghouse 113D (2N3432) (Date Code 434) is a silicon, fused, NPN, power transistor intended for use in voltage and current regulation, amplifiers, and high-power switching circuit applications.

OBJECTIVE OF TEST

To determine the capabilities and limitations of the Westinghouse 113D (2N3432) Transistors and their performance during the tests conducted as outlined in SDM03501A and SDM03501A/33 specifications.

CONCLUSIONS

The units, with limitations, met the requirements of SDM03501A specification. These units should not be utilized to the extreme environmental levels such as may be encountered in Group B Tests, Subgroup 4, of this test program which stresses the units beyond the manufacturer's specifications.

RECOMMENDATIONS

It is recommended that the proposed mounting of these devices be tested thoroughly so that temperature dissipation will not overheat the junction.

Distribution of Test Samples

<u>Test</u>	<u>Sample S/N's</u>
"A" Group Test	1 - 90
Operating Life	71, 72, 76, 78, 79, 3, 4, 5, 7 and 10
Storage Life	11 - 20
Altitude	21 - 30
Moisture Resistance	
Solderability	31 - 40
Acceleration	
Shock	
Vibration	
Power Cycling	41 - 50
Thermal Shock	
Tensile Strength	
Sequentially through all tests	61 - 70
Control Group and <u>Spares</u>	71 - 80
Test Set-up and Check Out	81 - 90

TABLE I
Performance Requirements

Measurement	Symbol	Condition	Min.	Max.	Units
Collector Current	I_{CEX}	$V_{BE} = -1.5 \text{ Vdc}$, $V_{CE} = 200 \text{ Vdc}$, $T_C = +150^\circ\text{C}$	20		mA
Emitter Current	I_{EBO}	$V_{EB} = 25 \text{ Vdc}$, $I_C = 0$, $T_C = +150^\circ\text{C}$	20		mA
Saturation Resistance	$r_{CE(\text{sat})}$	$I_C = 5.0 \text{ A}$, $I_B = 750 \text{ mA}$, $T_C = +25^\circ\text{C}$	0.5		ohm
DC Current Gain	h_{FE}	$V_{CE} = 4 \text{ Vdc}$, $I_C = 5A$, $T_C = -25^\circ\text{C}$	10	18(typ)	
Beta Cutoff Frequency	f_{hfe}	$V_{CE} = 4 \text{ Vdc}$, $I_C = 5A$, $T_C = +25^\circ\text{C}$, $I_{n(A)} = 1 \text{ mA rms}$	30(typ)		kc

TABLE II
GROUP B TESTS

<u>Test</u>	<u>Method</u>	<u>Condition</u>
	MIL-STD-750	
<u>Subgroup 1</u>		
Operating Life Post-Test End-Point Measurements	1026	Para 4.3.1 Table IV of the applicable detail specification
<u>Subgroup 2</u>		
High Temperature Life (Storage Life) Post-Test End-Point Measurements	1031	Para 4.3.2 Table IV of the applicable detail specification
<u>Subgroup 3</u>		
Altitude Moisture Resistance Post-Test End-Point Measurements	1001 1021	Para 4.3.3 Para 4.3.4 Table IV of the applicable detail specification
<u>Subgroup 4</u>		
Solderability Constant Acceleration Shock Vibration, Variable Frequency Post-Test End-Point Measurements	2006 2016 2056	Para 4.3.5 Para 4.3.6 Para 4.3.7 Para 4.3.8 Table IV of the applicable detail specification
<u>Subgroup 5</u>		
Power Cycling Thermal Shock Terminal Strength Post-Test End-Point Measurements	1052 1056 2036	Para 4.3.9 Para 4.3.10 Para 4.3.11 Table IV of the applicable detail specification

TABLE III

Post-Test End-Point Measurements

<u>Parameter</u>	<u>Symbol</u>	<u>All allowable Deviation</u>	<u>Min.</u>	<u>Max.</u>
Collector Current	I_{CEX}	$\pm 1.0 \text{ mA}$		
DC Current Gain	h_{FE}		10	
Saturation Resistance	$r_{CE}(\text{sat})$			0.6 ohms

Note: The parameter measurements shall not deviate from the value obtained when tested before the environmental tests by more than the above limits.

VISUAL EXAMINATION (EXTERNAL)

The transistors were visually examined under a 10X microscope for quality of workmanship and mechanical soundness, including such factors as seals, soldering, coating, plating and product marking. Following the visual examination, ten of the samples were subjected to a physical dimensions check using standard measuring instruments, i.e., micrometer, caliper, etc., to insure that the semiconductors met the requirements of the applicable detail specification.

RESULTS

On S/N 91 the part number was illegible and on S/N 92 the manufacturer's date code was illegible.

All physical dimensions were found to be within the specified limits of the outline drawing in the detail specification, Figure 1, Dimensional Outline, Transistor 113D.

VISUAL EXAMINATION (INTERNAL)

One semiconductor device was opened and examined with a 10X microscope to determine construction.

RESULTS

These transistors are of single chip construction in planar form with the emitter diffused into the base region and the base in turn diffused into the collector region. The chip is welded to the case over the stud, while leads for the base and emitter are welded to their respective locations on the chip and connected to feed-through terminals on the case header. The transistor is constructed in angular form with a portion of the base in the center surrounded by the emitter which in turn is surrounded by the rest of the base which is surrounded by the collector. The central portion of the base and the remainder of the base ring are connected by a jumper strap. It was also noted that the emitter had a jumper strap connected at one point to another point 180° around the emitter ring. The angular alignment of the emitter and base jumper straps was approximately 90°. The axis of the emitter jumper strap which lies approximately between the emitter base lead was taken as the Z axis, while the axis of the base jumper, which lies at 90° to the emitter jumper, was taken as the X axis. The Y axis lies perpendicular to the plane of the base, and consequently perpendicular to the plane of the jumpers.

There were no apparent imperfections noted in the construction of the welds or header seals.

SEAL-LEAK TEST

The semiconductors were subjected to a Leak Test by NASA, employing a radioactive tracer gas at a pressure differential of 80 ± 5 psi.

TEST RESULTS

S/N's 93-100 failed and were retained by NASA per AEC regulations.

GROUP A TESTS

ELECTRICAL TESTS

TEST PROCEDURE

The transistors were subjected to all the electrical performance requirements as set forth in Table I of this report. The tests were performed in accordance with SEMI03501A/33 and MIL-STD-750 methods were incorporated. In the case of any parameter measurement falling within the measurement accuracy of the instrument, the sample was considered within specification limits.

Because of the nature of the devices and the parameters to be measured, $r_{C(plate)}$, h_{FE} , and $f_{T(sat)}$, the devices were securely mounted to a large heat sink so that the case temperature would be held at $+25^{\circ}\text{C}$ during the measurements. The test procedures were arranged so that the bias conditions were applied to the device for a minimum period of time.

TEST RESULTS

S/N 2 failed I_{CEX} (shorted).
S/N 1 failed I_{BO} (shorted).
S/N 82 failed $f_{T(sat)}$ (shorted).
S/N's 1 and 83 failed h_{FE} .

GROUP B TESTS

Following the Group A Electrical Tests, the test samples were broken into five subgroups. Each subgroup was subjected to the tests as outlined in Table II and End-Point measurements as outlined in the detail specifications were performed following each subgroup and at specified times during the tests of Subgroups 1 and 2.




Figure 1
Operating Life Test Circuit

GROUP B TESTS

SUBGROUP 1

OPERATING LIFE TEST

TEST PROCEDURE

The test samples were subjected to 2000 hours Operating Life at case temperature of +88°C and a power dissipation of 83 watts. The units were removed from test and the End-Point measurements performed at 100, 250, 500, 1000, 1500 and 2000 hours. The circuit used during this test is shown in Figure 1.

In an attempt to establish a test condition of $T_C = +37^\circ\text{C}$ and $P_J = 150 \text{ W}$, four units were destroyed, S/N's 6, 8, 9 and 90. The cause was determined to be excessive junction temperature. It was determined that the thermal resistance between the case and the heat sink could not be reduced sufficiently to maintain a case temperature of +37°C with a power dissipation of 150 watts and a sink temperature of +25°C. Consequently, the test conditions were modified so that the thermal resistance between case and sink was taken into account and the junction temperature stabilized at the maximum specified junction temperature of +150°C. This in turn resulted in a power dissipation of 83 watts.

The heat sink used to stabilize case temperature for this test consisted of a 17"x17"x1/2" aluminum plate which formed one wall of a 17"x17"x6" water tank. The water temperature was thermostatically controlled so that the sink temperature could be maintained at +52°C.

Since $P_J = 83 \text{ W}$, $T_S = 52^\circ\text{C}$, $T_C = 88^\circ\text{C}$, $\theta_{C-S} = \frac{88-52}{83} \text{ C/W} = .42^\circ\text{ C/W}$. The case temperature was measured by inserting a thermocouple into a .060" diameter hole drilled into the hex portion of the case. The heat sink temperature was measured with a United Electric, Model E32N, temperature controller whose sensing element was attached diagonally across the heat sink. The transistor was prepared with Dow Corning heat sink compound, and torqued to the maximum recommended value of 30 lb.-in. No insulating washers were used in the mounting. All ten devices tested were mounted on the common heat sink, and were spaced 3" from one another on a 5x5 grid pattern. When the device failures occurred during the initial test set-up at 150W, only one device at a time was mounted on the heat sink. At a power dissipation of 150W, the case temperature would rise beyond 37°C to approximately 85°C, at which time failure would occur, while the sink temperature was maintained at or near 25°C. A thermocouple surface probe was also used to measure the sink temperature adjacent to the transistor. It was found that the heat sink temperature had increased to 28°C.

OPERATING LIFE TEST

(Continued)

TEST RESULTS

S/N 71 shorted out immediately following re-installation in the life rack after the 1500 hour End-Point measurements. Examination of the End-Point data revealed no reason for the failure. S/N 71 was removed from test.

S/N 72 exceeded the limit specified for Δ IC_{EX} at the 2000 hour End-Points.

SUBGROUP 2

STORAGE LIFE TEST

TEST PROCEDURE

The semiconductors were inserted into a Storage Life Test fixture and placed in a high temperature chamber and stabilized at 175°C for a period of 2000 hours. The semiconductors were removed from the chamber at the completion of 100, 250, 500, 1000, 1500 and 2000 hours for End-Point measurements.

TEST RESULTS

All units were within the specified limits.

SUBGROUP 3

ALTITUDE TEST

TEST PROCEDURE

The semiconductors were placed in an altitude chamber and the pressure was reduced to an equivalent of 200,000 feet of altitude. After the chamber had attained this altitude, measurement of IC_{BO} of the test samples was performed. The chamber was then returned to ambient pressure and measurement of IC_{BO} of the test samples was again performed.

TEST RESULTS

All samples were within the specified limits.

SUBGROUP 3

(Continued)

MOISTURE RESISTANCE TEST

TEST PROCEDURE

The semiconductors were placed in a moisture resistance chamber and subjected to ten humidity cycles per MIL-STD-750, Method 1021.

Upon completion of the test, the specimens were removed from the chamber and visually examined for evidence of damage as a result of the test, and Post-Test End-Point measurements were performed.

TEST RESULTS

All samples were within the specified limits.

SUBGROUP 4

SOLDERABILITY TEST

TEST PROCEDURE

The semiconductor terminals were immersed in Kester Soldering Flux, Formula #1544, to within 1/4" of the body of the devices. After this process, the units were immediately immersed in solder composed of 60 parts tin and 40 parts lead as specified in MIL-STD-202B, Method 210, Test Condition B.

TEST RESULTS

The units showed no evidence of physical damage, and solder covered more than 90% of the leads.

CONSTANT ACCELERATION TEST

TEST PROCEDURE

The semiconductors were mounted in a centrifuge and subjected to a constant acceleration of 20,000 g's for five minutes in each direction of the three mutually perpendicular axes. Following the Acceleration Test, the devices were visually examined for evidence of damage as a result of the test.

TEST RESULTS

The units showed no evidence of damage.

SUBGROUP 4

(Continued)

SHOCK TEST

TEST PROCEDURE

The semiconductors were mounted on a shock machine and subjected to five blows in each direction of the three mutually perpendicular axes. Each blow had an amplitude of 3500 g's in a half-sine waveform and a duration of 0.3 to 0.5 milliseconds. The semiconductors were energized during this test and the emitter potential was monitored to determine if there were any discontinuities or shorts of a duration greater than 50 nanoseconds, as outlined in the general specification. Following the Shock Test, the devices were visually examined for damage.

TEST RESULTS

S/N 31 indicated a discontinuity or short exceeding 50 nanoseconds during the second blow in the Y axis.

VIBRATION, VARIABLE FREQUENCY

TEST PROCEDURE

The semiconductors were inserted in a test fixture which, in turn, was mounted on the table of the vibration exciter. The units were then subjected to vibration in the frequency range of 10 to 3000 cycles and return to 10 cycles in a time duration of 22 minutes. A vibration level of 30 g's or .45" DA was maintained, whichever was the lesser. The units were subjected to two ~~cycles~~ as described above, along each of the three major axes.

The devices were energized during this test, and emitter potential was monitored to determine if there were any discontinuities or shorts with a duration greater than 50 nanoseconds, as outlined in the general specification.

Following the Vibration Test, the units were visually examined for damage, and Post-Test End-Point measurements were performed.

TEST RESULTS

Vibration:

Discontinuities or shorts were indicated as follows: S/N 31 in X and Y axis. S/N 34 in Y and Z axis. S/N 39 in X, Y and Z axis.

SUBGROUP 4
(Continued)

VIBRATION, VARIABLE FREQUENCY

TEST RESULTS (Continued)

End-Points:

S/N's 32 and 58 failed Δ I_{CEX}. (shorted)
S/N 58 shorted.
S/N's 31 and 55 failed I_{CE} (soft)

SUBGROUP 5

POWER CYCLING TEST

TEST PROCEDURE

The semiconductors were subjected to a Power Cycling Test under the following conditions:

The "Power-On" portion of the cycle was long enough to allow the semiconductor case temperature to reach $+150^{\circ}\text{C} \pm 5^{\circ}\text{C}$. The "Power-Off" portion of the cycle was long enough to permit the case temperature to drop within $\pm 5^{\circ}\text{C}$ of the ambient temperature. This cycle was repeated for a total of 500 cycles.

TEST RESULTS

S/N's 47 and 48 failed (shorted) after about 300 cycles.

THERMAL SHOCK TEST

TEST PROCEDURE

The semiconductors were subjected to five cycles of thermal shock, these conditions being five minutes at 100°C , alternated by five minutes of 0°C as per MIL-STD-750, Method 1036, Condition B.

TEST RESULTS

No physical damage was observed as a result of this test.

SUBGROUP 5
(Continued)

TERMINAL STRENGTH TEST

TEST PROCEDURE

Each semiconductor was subjected to a Terminal Strength Test with a 5 pound load for a 15 second duration, as specified in MIL-STD-750, Method 2036, Condition A.

At the conclusion of the test, the units were examined for evidence of damage, and Post-Test End-Point measurements were performed.

TEST RESULTS

No damage was noted as a result of the Terminal Strength Test.

During the Post-Test End-Point measurements, S/N's 44 and 51 failed Δ I_{CEX}. (shoved)

SEQUENTIAL TESTS

TEST PROCEDURE

Ten samples (S/N's 5, through 60) were placed in all of the tests of Subgroups 3, 4 and 5 in order. Following the End-Point measurements for Subgroup 5, half of this group was placed in Operating Life Test and the remaining half was placed in Storage Life.

End-Point measurements were performed on both groups at 100, 250, 500, 1000 and 1100 hours.

TEST RESULTS

Operating Life: S/N 55 failed Δ I_{CEX} at 250, 500 and 1100 hour End-Points.
S/N 52 failed upon restart after 100 hour End-Points.

Storage Life: S/N 57 failed Δ I_{CEX} at 250 and 500 hour End-Points.
S/N 59 failed Δ I_{CEX} at 1000 and 1100 hour End-Points.

ENCLOSURE 1

SUMMARY SHEET #1

Date Completed 2/3/65

No. of Samples 100

Sample Nos. 1 to 100

NACA Contr.

NACA

Mfr. Type 2N2432 (113D)

Date Test Begun 1/3/64

From 1 to 100

S/N 30M0351A33 Min. Weldinghouse

Test Item	Test No.	Spec. No.	Page	Date	Test Conditions	Specification Limits	Measured Values	No. Samples Passed	Remarks
143	6	1-100	4-2	2-10	Seal Leak Test	Max unless otherwise specified Atmospheric cc/sec in excess of 1×10^{-9} cc/sec.	Min. .035 mA Max. .20 mA+	100	92 S/N 91, 92 out
1	A	1-92	4-2	2-10	Visual Exam (Ext)	As per spec.		90	S/N 90
2	A	1-10	3-3	1	Physical Dimensions	As per spec.		10	S/N 2 out
3	A	1-90	4-1	3	Collector Current	Max. .20 mA		89	S/N 2 out in rest of assembly
4	A	1-3	4-1	3	I_{CEX}				
5	A	1-3	4-1	3	$V_{BE} = 1.5$ Vdc				
6	A	1-3	4-1	3	$V_{CE} = 200$ Vdc				
7	A	1-3	4-1	3	$T_C = +150^\circ C$				
8	A	1-3	4-1	4	Emitter Current	Max. .20 mA			
9	A	1-3	4-1	4	I_{EO}				
					$V_{EB} = 25$ Vdc				
					$I_C = 0$				
					$T_C = +130^\circ C$				
					$r_{CE}(50)$				
					$18 = 750$ mA				
					$I_C = 5$ A				
					$T_C = +250^\circ C$				
					Ratio Cut-off Freq	Max. .30 kc (typ)			
					f_{HC}	0 kc			
					$V_{CE} = 4$ Vdc				
					$I_C = 5$ A				
					$T_C = +250^\circ C$				
					$I_{n(A)} = 1$ mA rms				
					DC Current Gain	Min. 10 Max. 19 (typ)			
					h_{FE}	7			
					$V_{CE} = 4$ Vdc	32			
					$I_C = 5$ A				
					$T_C = +250^\circ C$				
					Visual Exam (Im)				Opened S/N 73 to determine construction

SUMMARY SHEET # 4									
Transistor		Contract		Date Completed		No. of Samples		Sample Nos.	
S-60C 30M6350A/33 Min.		Westinghouse		Mfr's Type 2N3432(1130)		Date Test Began 11/3/64		From 1 to 100	
Test Item	Sample No.	Proc. Step	Data Page	Test Conditions	Specification Limits Max unless otherwise specified		Measured Values	No. Sample Tested	Remarks
8	11-20 Table IV	20	1000 hr End-Points	Allow. Dev. \pm 1.0 mA Min. 10 Max. .5 ohms	.045mA 1.4 .074 ohms	.245mA 23 .104 ohms	10 10 10	10 10 10	
9	Sub 51-60 Grp 2			Δ ICEX I _{FE} 'CE(sat)					
11				1500 hr End-Points	Allow. Dev. \pm 1.0 mA Min. 10 Max. .5 ohms	.06mA 1.3 .07 ohms	.36mA 20 .198 ohms	10 10 10	
12	B 21-30 4.3.3	3	21	Δ ICEX I _{FE} 'CE(sat)	Allow. Dev. \pm 1.0 mA Min. 10 Max. .5 ohms	.08mA 1.5 .072 ohms	.46mA 22 .116 ohms	10 10 10	
13	Sub 51-60 Grp 3		22	2000 hr End-Points	Ambient (20mA Max) Altitude Test (20mA Max) Post Altitude (20mA Max)	.023mA .022mA .023mA	.4mA .4mA .4mA	20 20 20	
14	B 21-30 Table IV	3	23-24	Δ ICEX I _{FE} 'CE(sat)	Allow. Dev. \pm 1.0 mA Min. 10 Max. .5 ohms	.008mA 1.4 .058 ohms	.76mA 27 .126 ohms	20 20 20	
15	Sub 51-60 Grp 3			Solderability MIL-STD-202C Method 210 Condition B	90% of surface to be covered with smooth bright film of solder.			20	20

Item Transitions		Comm:		NASA		Westinghouse		Mf's Type 2N3432(13D)		Date Test Began	11/2/64	From	1 to 100	Sample Notes:
Spec:	50M05901A/233 MHz	Test No.	Proc No.	Date Proc.	Page	Test Conditions	Spec Location Label	Max unless otherwise specified	Measured Values	No. Samples	Tested	Passed	No. Samples	REMARKS
16	B	31-40	4.3.6			Constant Accel. 20,000 g's , 5 min. XYZ axes MIL-STD-750 Method 2006			Min. .50 nanoseconds	20	19	S/N 31 wa- ceeded 50 ns.		
16	Sub	51-60	Grp A			Shock MIL-STD-750 Method 2016			Max. .50 nanoseconds	20	19	S/N 31 wa- ceeded 50 ns.		
17	B	31-40	4.3.7			3500 g's , .3-.5 ms 5 blows XYZ axes			Min. .50 nanoseconds	20	17	S/N 31,34,39 exceeded 50ns		
18	Sub	51-60	Grp 4			Vibration Var. Freq. 0.45" DA or 30 g's 10-3000 cps , 2.22 min. sweeps XYZ axes			Max. .50 nanoseconds	20	17	S/N 31,34,39 exceeded 50ns		
19	B	31-40	4.3.8			MIL-STD-750 Method 2056			Min. .10	13	27	S/N 32 out		
19	Table	25-26	IV			Post-Test End-Point Δ I _{CEX}			Max. .5 ohms	.0008 ohms	3 ohms	S/N 38 shorted		
20	B	41-50	4.3.9			HFE TC(Fast)			Allow. Dev. ± 1.0 mA	.000mA	200mA	20	20	S/N 38 shorted
20	Sub	51-57	Grp 5			power Cycling MIL-STD-750 Method 1052						18	18	S/N 31,35,601
						On Time 1 min. Off Time 2 min. Temp +150°C 500 cycles						17	17	S/N 47,48 shorted

Item		Transistor		Cont:		NASA	Date Completed	2/5/65	No. of Samples	100	Sample No.
						Mfr:	Type	2N3432(113D)	Date Test Begin	11/3/64	From 1 to 100
									Measured Values		
									Min	Max	
									Tested	Passed	
									20	20	
Test		Test No.	Sample Nos.	Price	Page	Date	Test Conditions	Specification Limits	Measured Values	No. Samples Tested	Results
								Max unless otherwise specified	Min	Max	
21	B	41-50-4	310				Thermal Shock				
		Sub	51-60	Grp	5		MIL-STD-750 Method 1056 Condition B +100°C 5 min. 0°C 5 min. 5 Cycles				
22	B	41-50-4	211				Terminal Strength				
		Sub	51-57	Grp	5		MIL-STD-750 Method 2036 5 lb. for 15 sec. on each lead.				
23	B	41-46	Table	27-28			Post-Test End-Points	Allow. Dev. \pm 1.0 mA	.000mA	.200mA	17 15
		49-50	W				Δ ICEX hFE rCE(sat)	Min 10 Max .5 ohms	10	22	17 17
24	B	52-55	4	31			Operating Life Sust		.054 ohms	.152 ohms	17 17
		52-55	Table				MIL-STD-750 Method 1026 1C = 88°C PT = 83W				
25	B	52-55	Table	29			100 hr End-Points	Allow. Dev. \pm 1.0 mA	.02mA	.30mA	4 4 4
		52-55	W				Δ ICEX hFE rCE(sat)	Min 10 Max .5 ohms	17	.09 ohms	
30							250 hr End-Points	Allow. Dev. \pm 1.0 mA	.02mA	.1mA	3 2
							Δ ICEX hFE rCE(sat)	Min 10 Max .5 ohms	16	.28	3 3
									.052 ohms	.108ohms	3 3

S/N 52 shorted
on repeat

S/N 55 cut

SUMMARY SHEET # 6

Date Completed 2/5/65

No. of Samples 100 Sample Nos. 100

Date Test Began 11/3/64

From 1 to 100

Contract NASA

Spec. 20M03501A/33 Min.

Westinghouse

NPN's Type 2N3432(113D)

Item	Institution	Proc. No.	Page	Data Page	Test Conditions	Specification Limit Max unless otherwise specified	Measured Voltage Max	No. Samples Tested	Remarks
26	8	56,7 59,60	Table IV	33	Storage Life Seq. 1100 hr End-Points ▲ ICEX HFE CE(salt)	Allow. Dev. \pm 1.0 mA Min. 10 Max. .5 ohms	.03mA .15 .082 ohms	2,44mA 19 .112 ohms	3 4 4

ENCLOSURE 2

CONTINENTAL TESTING LABORATORIES, INC.

Spec. SOD3301A/33

Ref. Spec. MIL-SID-730

Test Program NASA

Report No. - 11253-8-1

Job No. C111-8

Manufacturer Westinghouse

Transistor Type 2N3432 (U13D)

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

Parameter Measurement

Symbol

Transistor Serial Number

Range

Limit

Max Min

Sec

SOMOSKA, A. J.

Spec. 500001A-13

Ref. Spec. MIL-STD-20

CIRCUIT TESTING LABORATORIES, INC.

Test Program - NASA

Top No.

CIN-8

Wastegate

Transistor Type: 2N3422U2D

Report No.: 11253-8-1

Parameter Measurement

Symbol

Test

Condition

Test

Condition

Test

Condition

Test

Visual Examination

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

Spot Leck Test

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

Seals

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

Soldering

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

Coatings

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

Plating

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

Welds

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

Product Marking

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

Collector Current

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

VBE = 5 Vdc

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

VCE = 200 Vdc

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

IC = 1156°

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

Emitter Current

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

VBE > 25 Vdc

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

IC = 0

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

IC = 1150°C

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

Solution Resistance

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

IC = 750 mA

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

IC = 255°C

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

IC = 3.0 A

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

HFE

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

DC Current Gain

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

VCE = 4 Vdc

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

IC = 5A

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

IC = 125°C

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

Beta Cut-off Frequency

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

11

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

10

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

14

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

14

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

14

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

14

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

14

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

14

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Test

14

Test

Condition

Test

Condition

Test

Condition

Test

Condition

Job No.: CIN-3

Spec. 50MM350A/33

Ref. Spec. MIL-S10-250

CONTINENTAL TESTING LABORATORIES, INC.

Spec.

50MM350A/33

Manufacturer: Westinghouse

NASA

Test Program

Report No. 11253-02

Test Strip #	Test Date	Parameter Measurement and Test Condition	Symbol	Transistor Serial Number	Test			Range	Limits	Test								
					11	62	63	64	65	66	67	68	69	70	Min Max	Mid Max	Min Max	Mid Max
A	11/14/64	Seal Leak Test													100°C vac	20 mbar	100°C vac	20 mbar
		Visual Examination			V	V	V	V	V	V	V	V	V	V				
		a. Seals																
		b. Soldering																
		c. Coating																
		d. Plating																
		e. Welds																
		f. Product Marking																
		Performance Requirements																
		Collector Current	ICEX															
		VBE = -1.5 Vdc																
		VCE = 200 Vdc																
		TC = +150°																
		Emitter Current	IEBO															
		VBE = 25 Vdc																
		IC = 0																
		TC = +150°C																
		Common Emitter Performance	ICE (vol)															
		IC = 5.0 A																
		IC = 750 mA																
		TC = +25°C																
		Beta Cut-off Frequency	f _{HC}															
		DC Current Gain	hFE															
		VCE = 4 Vdc																
		IC = 5A																
		TC = +25°C																

8

卷之三

NASA

Test Program NASA Langley Research Center

Ref. Spec. Hill-SD-140

卷之三

NASA Test Program

CONTINENTAL TESTING LABORATORIES, INC.		Spec. Ref. Spec.		SOMAR 101A/33	
NASA Test Program		Report No. 11253-8-1		Test	
Parameter	Requirement	Sym.	Transistor Serial Number	RANGE	
and Test Condition	Symbol	71	72	73	74
Seal Leak Test					
Visual Examination					
a. Seals					
b. Soldering					
c. Coating					
d. Plating					
e. Welds					
f. Product Marking					
Performance Requirements					
Collector Current					
V _{BE} = 0.15 Vdc					
V _{CE} = 200 Vdc					
I _C = 140 ⁺					
V _{TB} = 25 Vdc					
I _C = 0					
I _C = +150%					
Strength Resistance					
(min)					
I _C = 120 mA					
I _C = 120 mA					
Base Voltage Frequency Response					
Hz					
DC Current Gain					
V _{CE} = 4 Vdc					
I _C = 100 mA					
I _C = 100 mA					

Manufacturer: Werringhause
Instrument Type: 2154B/1130

Test ID: 211-0
Report No.: 1153-6-A

Test Program: NASA
Ref. Spec.: MIL-STD-883

CONTINENTAL TESTING LABORATORIES, INC. Spec. 81043501A3

Parameter	Measurement and Test Condition	Symbol box	Transistor Serial Number	Range		Limit	Notes
				Min	Max		
Soil Test Unit				-	-	-	-
Symbol Formation				-	-	-	-
a. Seats				-	-	-	-
b. Scratches				-	-	-	-
c. Cracking				-	-	-	-
d. Plating				-	-	-	-
e. Wells				-	-	-	-
f. Product Markings				-	-	-	-
Performance Requirements				-	-	-	-
Collector Current	ICX			-	-	-	-
VBE = 1.5 Vdc				-	-	-	-
VCE = 20V Vdc				-	-	-	-
IC = 150 mA				-	-	-	-
IC = 300 mA				-	-	-	-
IC = 500 mA				-	-	-	-
IC = 700 mA				-	-	-	-
IC = 1A				-	-	-	-
IC = 1.5A				-	-	-	-
IC = 2A				-	-	-	-
IC = 2.5A				-	-	-	-
IC = 3A				-	-	-	-
IC = 4A				-	-	-	-
IC = 5A				-	-	-	-
IC = 6A				-	-	-	-
IC = 7A				-	-	-	-
IC = 8A				-	-	-	-
IC = 9A				-	-	-	-
IC = 10A				-	-	-	-
IC = 11A				-	-	-	-
IC = 12A				-	-	-	-
IC = 13A				-	-	-	-
IC = 14A				-	-	-	-
IC = 15A				-	-	-	-
IC = 16A				-	-	-	-
IC = 17A				-	-	-	-
IC = 18A				-	-	-	-
IC = 19A				-	-	-	-
IC = 20A				-	-	-	-
IC = 21A				-	-	-	-
IC = 22A				-	-	-	-
IC = 23A				-	-	-	-
IC = 24A				-	-	-	-
IC = 25A				-	-	-	-
IC = 26A				-	-	-	-
IC = 27A				-	-	-	-
IC = 28A				-	-	-	-
IC = 29A				-	-	-	-
IC = 30A				-	-	-	-
IC = 31A				-	-	-	-
IC = 32A				-	-	-	-
IC = 33A				-	-	-	-
IC = 34A				-	-	-	-
IC = 35A				-	-	-	-
IC = 36A				-	-	-	-
IC = 37A				-	-	-	-
IC = 38A				-	-	-	-
IC = 39A				-	-	-	-
IC = 40A				-	-	-	-
IC = 41A				-	-	-	-
IC = 42A				-	-	-	-
IC = 43A				-	-	-	-
IC = 44A				-	-	-	-
IC = 45A				-	-	-	-
IC = 46A				-	-	-	-
IC = 47A				-	-	-	-
IC = 48A				-	-	-	-
IC = 49A				-	-	-	-
IC = 50A				-	-	-	-
IC = 51A				-	-	-	-
IC = 52A				-	-	-	-
IC = 53A				-	-	-	-
IC = 54A				-	-	-	-
IC = 55A				-	-	-	-
IC = 56A				-	-	-	-
IC = 57A				-	-	-	-
IC = 58A				-	-	-	-
IC = 59A				-	-	-	-
IC = 60A				-	-	-	-
IC = 61A				-	-	-	-
IC = 62A				-	-	-	-
IC = 63A				-	-	-	-
IC = 64A				-	-	-	-
IC = 65A				-	-	-	-
IC = 66A				-	-	-	-
IC = 67A				-	-	-	-
IC = 68A				-	-	-	-
IC = 69A				-	-	-	-
IC = 70A				-	-	-	-
IC = 71A				-	-	-	-
IC = 72A				-	-	-	-
IC = 73A				-	-	-	-
IC = 74A				-	-	-	-
IC = 75A				-	-	-	-
IC = 76A				-	-	-	-
IC = 77A				-	-	-	-
IC = 78A				-	-	-	-
IC = 79A				-	-	-	-
IC = 80A				-	-	-	-
IC = 81A				-	-	-	-
IC = 82A				-	-	-	-
IC = 83A				-	-	-	-
IC = 84A				-	-	-	-
IC = 85A				-	-	-	-
IC = 86A				-	-	-	-
IC = 87A				-	-	-	-
IC = 88A				-	-	-	-
IC = 89A				-	-	-	-
IC = 90A				-	-	-	-
IC = 91A				-	-	-	-
IC = 92A				-	-	-	-
IC = 93A				-	-	-	-
IC = 94A				-	-	-	-
IC = 95A				-	-	-	-
IC = 96A				-	-	-	-
IC = 97A				-	-	-	-
IC = 98A				-	-	-	-
IC = 99A				-	-	-	-
IC = 100A				-	-	-	-
IC = 101A				-	-	-	-
IC = 102A				-	-	-	-
IC = 103A				-	-	-	-
IC = 104A				-	-	-	-
IC = 105A				-	-	-	-
IC = 106A				-	-	-	-
IC = 107A				-	-	-	-
IC = 108A				-	-	-	-
IC = 109A				-	-	-	-
IC = 110A				-	-	-	-
IC = 111A				-	-	-	-
IC = 112A				-	-	-	-
IC = 113A				-	-	-	-
IC = 114A				-	-	-	-
IC = 115A				-	-	-	-
IC = 116A				-	-	-	-
IC = 117A				-	-	-	-
IC = 118A				-	-	-	-
IC = 119A				-	-	-	-
IC = 120A				-	-	-	-
IC = 121A				-	-	-	-
IC = 122A				-	-	-	-
IC = 123A				-	-	-	-
IC = 124A				-	-	-	-
IC = 125A				-	-	-	-
IC = 126A				-	-	-	-
IC = 127A				-	-	-	-
IC = 128A				-	-	-	-
IC = 129A				-	-	-	-
IC = 130A				-	-	-	-
IC = 131A				-	-	-	-
IC = 132A				-	-	-	-
IC = 133A				-	-	-	-
IC = 134A				-	-	-	-
IC = 135A				-	-	-	-
IC = 136A				-	-	-	-
IC = 137A				-	-	-	-
IC = 138A				-	-	-	-
IC = 139A				-	-	-	-
IC = 140A				-	-	-	-
IC = 141A				-	-	-	-
IC = 142A				-	-	-	-
IC = 143A				-	-	-	-
IC = 144A				-	-	-	-
IC = 145A				-	-	-	-
IC = 146A				-	-	-	-
IC = 147A				-	-	-	-
IC = 148A				-	-	-	-
IC = 149A				-	-	-	-
IC = 150A				-	-	-	-
IC = 151A				-	-	-	-
IC = 152A				-	-	-	-
IC = 153A				-	-	-	-
IC = 154A				-	-	-	-
IC = 155A				-	-	-	-
IC = 156A				-	-	-	-
IC = 157A				-	-	-	-
IC = 158A				-	-	-	-
IC = 159A				-	-	-	-
IC = 160A				-	-	-	-
IC = 161A				-	-	-	-
IC = 162A				-	-	-	-
IC = 163A				-	-	-	-
IC = 164A				-	-	-	-
IC = 165A				-	-	-	-
IC = 166A				-	-	-	-
IC = 167A				-	-	-	-
IC = 168A				-	-	-	-
IC = 169A				-	-	-	-
IC = 170A				-	-	-	-
IC = 171A				-	-	-	-
IC = 172A				-	-	-	-
IC = 173A				-	-	-	-
IC = 174A				-	-	-	-
IC = 175A				-	-	-	-
IC = 176A				-	-	-	-
IC = 177A				-	-	-	-
IC = 178A				-	-	-	-
IC = 179A				-	-	-	-
IC = 180A				-	-	-	-
IC = 181A				-	-	-	-
IC = 182A				-	-	-	-
IC = 183A				-	-	-	-
IC = 184A				-	-	-	-
IC = 185A				-	-	-	-
IC = 186A				-	-	-	-
IC = 187A				-	-	-	-
IC = 188A				-	-	-	-
IC = 189A				-	-	-	-
IC = 190A				-	-	-	-
IC = 191A				-	-	-	-
IC = 192A				-	-	-	-
IC = 193A				-	-	-	-
IC = 194A				-	-	-	-
IC = 195A				-	-	-	-
IC = 196A				-	-	-	-
IC = 197A				-	-	-	-
IC = 198A				-	-	-	-
IC = 199A				-	-	-	-
IC = 200A				-	-	-	-
IC = 201A				-	-	-	-
IC = 202A				-	-	-	-
IC = 203A				-	-	-	-
IC = 204A				-	-	-	-
IC = 205A		</td					

CONTINENTAL TESTING LABORATORIES, INC.			Spec.	50MKA91A/33
Job No.	CIN-8		Ref. Spec.	MIL-STD-704
Manufacturer	Westinghouse	Test Program	NASA	
Transistor Type 2N1432 (111D)				Report No. 11253-8-1
Test Serial Number				Test
Test Ser. No.	Test Date	Parameter Measurement and Test Condition	Symbol	Range Limit
B 100	10/10/64	500 hr. OPERATING LIFE	71 72 73 74 75 76 77 78 79 70	Min Max Min Max Min Max Min Max
Post Test P.D. Points				Allowable Deviation in mils
Collector Current				100. 10. 10. 10. 10. 10. 10. 10. 10. 10.
VBE = +1.5 Vdc VCE = 200 Vdc IC = 150°C				10. 10. 10. 10. 10. 10. 10. 10. 10. 10.
DC Current Gain				10. 10. 10. 10. 10. 10. 10. 10. 10. 10.
VCE = 4 Vdc IC = 5A TC = +25°C				10. 10. 10. 10. 10. 10. 10. 10. 10. 10.
Saturation Resistance				0.6 ohms
ICF (mA)				100.
IC = 5.0 A IB = 150 mA VC = +25°C				10. 10. 10. 10. 10. 10. 10. 10. 10. 10.
B 100				10. 10. 10. 10. 10. 10. 10. 10. 10. 10.
B 100				10. 10. 10. 10. 10. 10. 10. 10. 10. 10.
B 100				10. 10. 10. 10. 10. 10. 10. 10. 10. 10.

CHINA'S GREEN REVOLUTION

CONTINENTAL TESTING LABORATORIES, INC., Spec. No. 1001-A-3

WANTAGE & TUNBRIDGE WELLS - Westinghouse

NASA

204321113D

Report No. 253-87

20

As a result, the number of people who have been infected with the virus has increased rapidly, and the number of deaths has also increased.

As a result, the number of people who have been infected with the virus has increased rapidly, and the disease has spread to many countries around the world.

卷之三

卷之三

ENTRAL TESTING LABORATORIES, INC.
BOSTON, MASS.

Spec. No. 5541501A-13
Ref. Spec. No. 510-790

卷之三

卷之三

卷之三

EXPERIMENTAL TESTS OF LANDSCAPE HETEROGENEITY

Spec. 3 MADAGASCAR

卷之三

Report No. 1253-6-1

10

JOURNAL OF CLIMATE

CONTINENTAL TESTING LABORATORIES, INC.

Spec. No. 3501A/33

卷之三

Test Program

Ref. Spec. MIL-S-1B-750

JOB NO. CIN-8

CONTINENTAL TESTING LABORATORIES, INC.

Spec. 50M3501A/33

MANUFACTURER: Westinghouse

Test Program: NASA

Ref. Spec.: MIL-STD-750

Transistor Type: 2N442 (NPN)

Report No. 1125-S-2

Test

Plot No.	Date and Test Condition	Symbol	Transistor Serial Number	Range	Limit															
			11	12	13	14	15	16	17	18	19	20	Min	Max	Hin	Hin	Hin	Hin	Hin	
B	100% H�A 50KHz 1V _C	ICEX																		
C	Post-Test End Points	ICEX																		
D	Collector Current V _{BE} = 1.5 Vdc V _{CE} = 200 Vdc T _C = +150°C	I _{CE}	13	.62	.74	.39	.41	.33	.41	.34	.41	.31	.31	.31	.31	.31	.31	.31	.31	
E	DC Current Gain V _{CE} = 4 Vdc I _C = 5A T _C = +25°C	H _{FE}	16	16	16	20	21	22	23	17	14	14	14	14	14	14	14	14	14	
F	Saturation Resistance I _C = 5.0 A I _C = 7.50 mA T _C = +425°C	(I _{CE}) (mA)	.168	.164	.164	.164	.164	.164	.164	.164	.164	.164	.164	.164	.164	.164	.164	.164	.164	.164
G																			0.0 ohm	

Allowable
Deviation
±1mA

CONTINENTAL TESTING LABORATORIES, INC.

33-B8B-4

卷之三

TEST PROGRAM

卷之三

RELIABLE! TRUSTED! TESTING LABORATORIES, INC. Spec. 50-1653501-A-1

CONTINENTAL TESTING LABORATORIES, INC.

卷之三

卷之三

卷之三

JOB NO. CIN-8

Manufacturer Westinghouse

CONTINENTAL TESTING LABORATORIES, INC.

Spec. SAE 50M3501A/3

Ref. Spec. MIL-STD-750

Report No. 11251-8-7

Test

Test Step	Tech Date	Parameter Measurement and Test Condition	Symbol	Transistor Serial Number								Range Limits		Min Max				
				51	52	53	54	55	56	57	48	59	60	Min	Max			
B	11/26/64	Collector Resistance COPPER & RUGGED SUBSTRATE	$\frac{V}{I}$	2.0	2.1	2.2	2.3	2.4	2.5	2.6	2.7	2.8	2.9	2.0	2.8			
B	11/26/64	Post-Test End-Points Collector Current $V_{BE} = -1.5$ Vdc $V_{CE} = 200$ Vac $T_C = +150^\circ\text{C}$	I_{CEX}	.022	.020	.021	.022	.023	.024	.025	.026	.027	.028	.029	.020	.028		
B	11/26/64	DC Current Gain $V_{CE} = 4$ Vac $I_C = .5A$ $T_C = +25^\circ\text{C}$	H_F	.070	.072	.071	.073	.074	.075	.076	.077	.078	.079	.070	.071	.070	.079	
B	11/26/64	Saturation Resistance $I_C = 5.0$ A $I_C = 750$ mA $T_C = +25^\circ\text{C}$	$ ICE _{sat}$.069	.070	.071	.072	.073	.074	.075	.076	.077	.078	.079	.070	.079	.070	.079

Transistor Type 2N3472 (113D)

Parameter Measurement and Test Condition

 I_{CEX} H_F $|ICE|_{sat}$ Allowable Deviation
1.1 mA

卷之三

卷之三

CONTINENTAL TESTING LABORATORIES, INC.

Spec. No. 104053/1A 33
Ref. Spec. Mill. 510-750

JOB NO. 511-B

CONTINENTAL TESTING LABORATORIES, INC.

Spec. 30M3501A-33
Ref. Spec. MIL-SPEC-126

Manufacturer Westinghouse

Test program NASA

Test Allocable
Deviation
±1 mA

Transistor Type 2N3432 (113B)

Report No. 11259-87

Saturation Resistance

Post-Test Test Point	Parameter Measurement and Test Condition	Symbol	Transistor Serial Number								Range	Limits		
			51	52	53	54	55	56	57	58	59	60	Min Max	
12	AC _c Shock (Contract & Hold)	I _{CEx}	.086	.17	.25	.25	.25	.25	.25	.25	.25	.25	.086 .25	
13	DC Current Gain (V _{CE} = 4 Vdc, I _C = 3A, T _C = +25°C)	I _{FE}	1.0	1.0	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.25	1.0 1.25	
14	Saturation Resistance	I _{CE} (sat)	.086	.19	.22	.22	.22	.22	.22	.22	.22	.22	.22	.086 .22
15			.086	.17	.25	.25	.25	.25	.25	.25	.25	.25	.086 .25	
16			.086	.27	.45	.45	.45	.45	.45	.45	.45	.45	.086 .45	
17			.092	.21	.24	.24	.24	.24	.24	.24	.24	.24	.092 .24	
18			.076	.15	.41	* 200 * SHUNTS	* 200 *	* 200 *	* 200 *	* 200 *	* 200 *	* 200 *	.076 .41	
19			.102	.17	.123	.123	.123	.123	.123	.123	.123	.123	.102 .123	
20			.088	.17	.123	.123	.123	.123	.123	.123	.123	.123	.088 .123	
21			.086	.18	.24	.24	.24	.24	.24	.24	.24	.24	.086 .24	
22			.079	.3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	.079 3.0	
23														
24														

125

卷之三

THE JOURNAL OF CLIMATE

ROMANIA

卷之三

三

10

THERMOPHILIC BACTERIA

Report No. 1123-02

卷之三

Transistor Type... 2N3422 (1132)		CONTINENTAL TESTING LABORATORIES, INC.										Spec. MIL-STD-729					
Test Ctry.	Test Date	Parameter Measurement and Test Condition		Transistor Serial Number								Range		Limit			
		Symbol	Value	31	32	33	34	35	IC	37	38	39	40	Min	Max	Min	Max
B	10-10-64	A IC = 5.0 A		1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3	1.3
B	10-10-64	B V _{BE} = 0.750 volt		0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75
B	10-10-64	C V _{CE} = +150°C		150	150	150	150	150	150	150	150	150	150	150	150	150	150
B	10-10-64	D IC = 5A		5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
B	10-10-64	E IC = +25°C		25	25	25	25	25	25	25	25	25	25	25	25	25	25
B	10-10-64	F Saturation Resistance		1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
B	10-10-64	G IC = 5.0 A		1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
B	10-10-64	H IC = 750 mA		1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
B	10-10-64	I IC = +25°C		1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2	1.2
Post-Test End-Points		Collector Current		ICEX	*	*	*	*	*	*	*	*	*	*	*	*	*
V _{BE} = ~1.5 Volts		V _{CE} = 200 Volts															
IC = +150°C		IC = 5A															
IC = 4 Volts		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A															
IC = 750 mA		IC = 5A															
IC = +25°C		IC = 5A															
Saturation Resistance		IC = 5A				</td											

卷之三

50

卷之三

CONTINENTAL TESTING LABORATORIES, INC. Spec. 8843(6A)3

THE PROLOGUE

三

卷之三

卷之三

CONTINENTAL TESTING LABORATORIES, INC.

WERNER

卷之三

卷之三

MIL-SYD-73

卷之三

CHIEF EXECUTIVE OFFICER - CHIEF FINANCIAL OFFICER
CHIEF INFORMATION OFFICER - CHIEF OPERATING OFFICER

SUGAR INDIA

卷之三

卷之三

卷之三

卷之三

文獻

SPECIFIC

Test	Parameter Measurement and Test Condition	Symbol	Transistor Serial Number	Range	Limit Min Max
1	100 MA and 100V (Collector + Emitter)	S2	52 53 54 55 56 57 58 60	MIN MAX	MIN MAX
2	OPERATING LIFE TEST				
3	52, 53, 54, 55, 56, 57, 58, 59, 60				
4	52, 53, 54, 55, 56, 57, 58, 59, 60				
5	Post-Test End-Points Collector Current	I _{CX}			
6	V _{BE} = -1.5 Vdc V _{CE} = 200 Vdc T _C = +150°C		4 I _{CEX}	.02	.02
7	DC Current Gain V _{CE} = 4 Vdc T _C = 5A T _C = +25°C	I _{FE}	.31 .26 .15 .07 .60 .24 .24 .16 .20 .17	.06 .06 .07 .07 .30 .26 .26 .18 .22 .18	.06 .06 .07 .07 .30 .26 .26 .18 .22 .18
8	Saturation Resistance T _C = 5.0 A I _G = 750 mA T _C = +25°C	R _{CE} (Ω)	1.0 1.0 1.0	1.0 1.0 1.0	1.0 1.0 1.0

卷之三

CONTINENTAL TESTING LABORATORIES, INC.

Spec. 50403 H.A. 34

卷之三

卷之三

卷之三

THE INDIAN CHIEF

卷之三

CONTINENTAL TESTING LABORATORIES, INC.

Specie 30 AND 31 A/31

卷之三

Test Program NASA

卷之三

Ref. Spec. No. 310-730

JOE NY
C-14-B

Manufacture
Westinghouse

CONTINENTAL TESTING LABORATORIES, INC.

Spec. - SODISOL A 33

NASA

Ref. Spec. - MIL-STD-750

Test Program Report No. 11253-8-2

Test

Test Item	Parameter Measurement and Test Condition	Symbol	Transistor Serial Number						Range	Limits
			54	55	56	57	58	60		
1	V _E = 0.5 Volts V _C = 125 Volts T _C = +150°C	V _E	0.50	0.50	0.50	0.50	0.50	0.50	0.50	0.50
2	DC Current Gain V _C = 4 Vdc I _C = 5A T _C = +25°C	I _C	5.0	4.9	4.9	4.9	4.9	4.9	4.9	4.9
3	Conduction Resistance I _C = 5.0 A V _C = 750 mA T _C = +25°C	R _{CE} (mΩ)	1.22	0.66	0.99	1.19	0.89	0.68	0.66	0.66
4	Collector-to-Emitter Breakdown Voltage V _C = 125 Volts T _C = +150°C	V _{BR}	125	125	125	125	125	125	125	125
5	Non-Linearity End-Point Collector Current	I _{CE}	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
6	Collector-to-Emitter Breakdown Voltage V _C = +1.5 Vdc V _E = 200 Volts T _C = +150°C	V _{BR}	125	125	125	125	125	125	125	125
7	DC Current Gain V _C = 4 Vdc I _C = 5A T _C = +25°C	I _C	5.0	4.9	4.9	4.9	4.9	4.9	4.9	4.9
8	Conduction Resistance I _C = 5.0 A V _C = 750 mA T _C = +25°C	R _{CE} (mΩ)	1.22	0.66	0.99	1.19	0.89	0.68	0.66	0.66

F-2

Job No. SIN-8

CONTINENTAL TESTING LABORATORIES, INC.

Spec. 50M350A/03

MIL-STD-750

Manufacturer Westinghouse

Test Program NASA

Ref. Spec. MIL-STD-750

Transistor Type 2N3432 (100)

Report No. 11253-8

Test

Transistor Serial Number	Range	Limits
Symbol	Min	Max
I_{CBO}	.01	.01
V_{BE}	.5	.5
$V_{CE} = 250$ Vdc	.5	.5
$T_C = +15^{\circ}\text{C}$.5	.5
DC Current Gain	.01	.01
$V_{CE} = 4$ Vdc	.01	.01
$I_C = .5$ A	.01	.01
$T_C = +25^{\circ}\text{C}$.01	.01
Saturation Resistance	.01	.01
$I_C = .5$ A	.01	.01
$V_{CE} = 750$ mV	.01	.01
$T_C = -25^{\circ}\text{C}$.01	.01

FINAL EXAM

ENCLOSURE 3

RECD BY WUX YOUNGWOO DEPTN 6 440P EDT

FLOYD C KINNEY, CONTINENTAL TESTING LABORATORIES

FERNS PARK, FLORIDA

COPY FOR BARBAG WESTINGHOUSE HUNTSVILLE & FLOYD C KINNEY CONTINENTAL
TESTING LAB ORLANDO FLORIDA, WESTINGHOUSE 1130 /2N3432/ TRANSISTORS

QUALIFICATION SHOULD QUALITY CONCLUSION IN SUMMARY ON PAGE 4 TO NOTE
THAT GROUP A TESTS SUR GROUP 4 LIMITS EXCEEDED LIMITS GUARANTEED AT
WESTINGHOUSE AND ALSO SHOCK LEVEL OF 350G EXCEEDS VALUE ON MSFC STD
S-SPEC IN ALL OTHER RESPECTS REPORT IS ACCEPTABLE THANK YOU FOR
SENDING COPY OF REPORT TO US IF I CAN BE OF FURTHER SERVICE PLEASE
LET ME KNOW

LUTHER HARRISON WESTINGHOUSE ELECTRIC CORP YOUNGWOOD PA

NOTE: FORM AND PRINTED (AUGUST 1960)

NOTICE—When Government drawings, specifications, or other data are used for any purpose other than in connection with a contract under which a Contractor is engaged to furnish material, equipment, supplies, or services to the United States Government, the Contractor shall not thereon, nor on any part thereof, nor on any drawing whatsoever, and shall not cause the Government name to appear, or in any way, inscribed on the said drawings, specifications, or other data, or to be reproduced, or otherwise, or by any means, or in any manner, bearing the name or any other name or mark or signature, or conveying any right or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

APPLICATION	PART NO.	REV F	REVISIONS		
NEXT ASSY	USED ON	SYM	DESCRIPTION	DATE	APPROVAL

SEMICONDUCTOR DEVICE 113D, (IN3432)

DETAIL TEST SPECIFICATION FOR

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES: ± .001 IN. FRACTIONAL: DECIMAL: INCHES	ORIGINAL DATE OF DRAWING 7-31-64	GEORGE C. MARSHALL SPACE FLIGHT CENTER NATIONAL AERONAUTICS AND SPACE ADMINISTRATION MONTGOMERY, ALABAMA
MATERIAL	DRAFTSMAN CHECKER TECHNICIAN ENGINEER SUBMITTER	SEMICONDUCTOR DEVICE 113D, DETAIL TEST SPECIFICATION FOR
HEAT-TREATMENT	APPROVED	SCALE
FINISHES, SURFACES, FINISH	UNIT WT	CWG SIZE A
		SHEET 1 OF 2

REVISIONS

SYM	DESCRIPTION	DATE	APPROVAL
-----	-------------	------	----------

SCOPE

3.1 Description. - This specification covers the electrical and environmental characteristics requirements for silicon, fused, NPN, power transistor, Part Number 113D, intended for use in voltage and current regulators, amplifiers, and high-power switching circuit applications.

3.2 APPPLICABLE DOCUMENTS

3.2.1 The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issue and revision in effect on the date of testing shall apply.

SPECIFICATIONS

4.0M01501A

Semiconductor Devices, General Test Specification for

3. REQUIREMENTS

3.1 Requirements. - Requirements shall be in accordance with Specification 40M01501A and as specified herein.

3.2 Design and Construction. - Semiconductors shall be of the design, construction, and physical dimensions specified on figure 1.

3.3 Maximum Ratings. - The maximum ratings shall be as specified in table I.

3.4 Performance Requirements. - Performance requirements shall be as specified in table II.

3.5 EXAMINATIONS AND TESTS

4.1 Test Values and Conditions. - Table III shall be used in conjunction with the examinations and tests contained in section 4 of Specification 40M01501A.

4.2 Post-Test End-Point Measurements. - Post-test end-point measurements shall be made as specified in table IV.


CODE	DRG
PRINTING SIZE	40M01501A-3X

A

SHEET

REVISIONS

SYM	DESCRIPTION	DATE	APPROVAL



NOTES:

1. ANGULAR ORIENTATION AND SHAPE OF TERMINALS
NOT DEFINED.

2. RECOMMENDED STUD MOUNTING TORQUE: DRY, 20 - 30
INCH LB.; LUBRICATED, 12 - 18 INCH LB.

Figure 1. Dimensional Outline, Transistor 113D

CODE	DWG	
IDENT NO	SIZE	S-M03501A/13
A	SHEET	3

REVISIONS

SYM	DESCRIPTION	DATE	APPROVAL
-----	-------------	------	----------

Table I. Maximum Ratings

Measurement	Symbol	Rating
<u>Current</u>		
Collector Current	I_C	7.5 A
Base Current	I_B	5.0 A
Emitter Current	I_E	7.5 A
<u>Dissipation</u>		
Total Device Dissipation, $T_C = +37^\circ C$	P_T	150 W
<u>Temperature</u>		
Junction Temperature	T_J	$+150^\circ C$
Storage Temperature Range	T_{stg}	$-65^\circ C$ to $+150^\circ C$
<u>Thermal Resistance</u>		
Junction to Case	θ_{JC}	$0.75^\circ C/W$
<u>Voltage</u>		
Collector-to-Emitter	V_{CE}	200 Vdc
Emitter-to-Base	V_{EB}	25 Vdc
Collector-to-Base	V_{CB}	

v_{CB} can be equal to or greater than V_{CE} .

CODE	10A	IDENTG SIZE	SCM03501A/33
A	SHEET	4	

REVISIONS

SYM	DESCRIPTION	DATE	APPROVAL

Table II. Performance Requirements

Measurement	Symbol	Condition	Min	Max	Units
Collector Current	I_{CEX}	$V_{BE} = -1.5 \text{ Vdc}$, $V_{CE} = 200 \text{ Vdc}$, $T_C = +150^\circ \text{C}$	20		mA
Emitter Current	I_{EBO}	$V_{EB} = 25 \text{ Vdc}$, $I_C = 0$, $T_C = +150^\circ \text{C}$	20		mA
Saturation Resistance	$r_{CE}(\text{sat})$	$I_C = 5.0 \text{ A}$, $I_B = 750 \text{ mA}$, $T_C = +25^\circ \text{C}$	0.5		ohm
DC Current Gain	β_{FE}	$V_{CE} = 4 \text{ Vdc}$, $I_C = 5A$, $T_C = +25^\circ \text{C}$	10	18 (typ)	
Beta Cutoff Frequency	f_{hfe}	$V_{CE} = 4 \text{ Vdc}$, $I_C = 5 \text{ A}$, $I_{(AC)} = 1 \text{ mA dc}$ $T_c = 25^\circ \text{C}$	30 (typ)		kc

Table III. Test Values and Conditions

Test	Condition	General Specification Reference
Gas Method	Pressure differential = $80 \pm 5 \text{ psig}$	Para. 4.2.2.1
Terminal Strength (Condition E)	5.0 \pm 0.5 pounds applied to each lead for three 90 ± 5 degree arcs to the case	Para. 4.3.11
Operating Life	$T_C = +37^\circ \text{C}$, $P_T = 150 \text{ W}$, Duration of test = 2,000 \pm 40 hr	Para. 4.3.1

CODE	DMG	50M03501A/33
IDENT NO.	SIZE	
A	Sheet	5

REVISIONS

SYM	DESCRIPTION	DATE	APPROVAL
-----	-------------	------	----------

Table III. Test Values and Conditions (Continued)

Test	Condition	General Specification Reference
High-Temperature Life	Temperature = +150° C. Duration of test = 2,000 hr	Para. 4.3.6
Power Cycling	Case temperature = +150° C. $V_{CE} = 20 \text{ V}$, $I_C = 7.5 \text{ A}$	Para. 4.3.9

Table IV. Post-Test End-Point Measurements

Parameter	Symbol	Allowable Deviation	Min	Max
Collector Current	I_{CEX}	$\pm 1.0 \text{ mA}$		
DC Current Gain	β_{FE}		30	40
Saturation Resistance	$r_{CE}^{(\text{sat})}$			0.6 ohm

Note: The parameter measurements shall not deviate from the value obtained when tested before the environmental tests by more than the above limits.

5. NOTES

- 5.1 The notes specified in Specification 50M03501A are applicable to this specification.

CODE IDENT NO	DWG SIZE	50M03501A/13
A	SHEET	6

Unclassified

When this document is no longer required
by your activity, DESTROY IT in accordance
with applicable security regulations.

DO NOT RETURN IT TO DDC

Unclassified